Item No.	Description of work	Unit	Rate	Quantity	Rates to be quoted
			Rs. a. p.		
16	T.W. shelves with frames and shutters, &c., complete	,,	1 0 0	75	
17	Chocolate painting, two coats	Sqr.	3 8 0	8·40	
18	Constructing sinks	No.	3 0 0	5	
19	Providing stone mortar and pestle complete, fixed	,,	5 0 0	5	
20	Flooring with 3" lime concrete 1½" cement concrete and cement plaster on top, &c., complete	Sqrs.	20 0 0	10·00	
21	Levelling ground	L.S.		Item	

Constructing One Unit of Latrine at Harihar.

Item No.	Description	Unit	Rate	Quantity	Rates to be quoted
			Rs. a. p.		
1	Earthwork excavation for foundation	C.yd.	0 3 0	4	
2	Stone in mortar foundations and basement	C.ft.	0 5 0	130	
3	Burnt brick in mortar superstructure	,,	0 4 6	193	
4	Chunam plastering, two coats	Sqr.	3 4 0	4·91	
5	Cement pointing with thread lines	,,	4 4 0	0·56	
6	White and colour washing, two coats	,,	0 4 0	5·47	
7	Cement plastering ½" thick	,,	8 0 0	0·80	
8	Tar washing, two coats	,,	2 8 0	0·63	
9	Flooring with 3" concrete 1" cement concrete and plaster ½" thick in cement	,,	20 0 0	0·38	
10	Fixing outlets and constructing drains	L.S.	10 0 0	Item	
11	Providing galvanised iron sheet tubs 12"×6" complete with tarring	Each	0 12 0	6	

L. A. H. WINCKLER,
Superintending Engineer.

OFFICE OF THE SUPERINTENDENT, POWER & LIGHT, MYSORE.

Notification dated the 7th July 1938.

Sealed tenders in triplicate will be received at the Office of the Superintendent, Power and Lighting, Mysore, superscribed with the name of the work mentioned below.

2. The plans connected with the work may be seen at the Office of the undersigned at all working hours. The copies if required will be made available on payment of Rs. 3 per set.

3. The tenders should be drawn up strictly in accordance with the specifications furnished, at the same time writing out the rates at which each item of work is executed in figures as well as in words, failing which no cognisance is taken of the tender. No items other than those noted in the statement should be included in the tender as the items include provision for all sundries, repairs to damaged masonry and painting the casings, boards lead cables, etc.

4. The materials to be used on the work should be of best manufacture conforming to the departmental wiring rules and the latest B. S. or A. I. E. E. specifications and mention should clearly be made of the manufacture and catalogue numbers of the materials offered. The T. W. planks, etc., to be used in the work should be well seasoned and free from cracks knots and white wood. The minimum width of the plank to be used to boards, etc., should not be less than 12 inches unless it is to make up the difference in size of the board required. In all cases lap joints should be adopted. In no case joints would be permitted to be put up diagonally for the boards.

5. The undersigned reserves the right to reject the tenders without assigning any reasons therefor.

6. The successful tenderer will be required to deposit an earnest money of Rs. 50 (Rs. fifty) and Rs. 45 (Rs. forty-five) on each of the works in cash and execute an agreement within a week from the date of intimation as to the acceptance of the tender, failing which the tender will be disposed of otherwise at his risk.

7. In executing the work, the wiring rules of this Department as well as those of the Institution of Electrical Engineers should be strictly followed.

8. The control switches, etc., should be fixed in inconspicuous corners and grouped. The successful tenderer should be prepared to carry out any changes in the location of the lighting fixtures, control points, etc., that might be suggested by the undersigned, during the course of work, without any extra cost, if the estimate is not materially affected by such deviations. The undersigned reserves the right also to reject the work in full or part if he finds the work not executed in terms of the specification.

9. Successful tenderer should send a board fitted with samples of all the materials offered in connection with the work to the undersigned and start the work only after obtaining approval for use of the same on the work.

10. It will be obligatory on the part of the tenderer to attend to any major troubles that might develop due to bad workmanship in cable joints, etc., within the period of first twelve months from the date of handing over the installation to this department free of any charges.

11. Name of Work.—Installing Electric Lights, etc., to the Railway Stations at Hole-Narasipur and Hole-Narasipur Town.

12. The last date and time for receiving the tenders is 25th July at 3 P. M.

13. The time and date for opening the tenders in public is 25th July at 4 P. M.

14. A period of one calendar month is the time within which the work is expected to be completed in all respects from the date of acceptance of the tender, failing which a penalty of Rs. 10 for each day of delay over and above the stipulated period will be enforced.

15. Details of work.—The quantities given in the statement below are not guaranteed and are subject to change during the execution of the work.

INSTALLING ELECTRIC LIGHTS TO THE RAILWAY STATION AT HOLE-NARASIPUR.

	Particulars	*Quantity*	
	Part I—Exterior Work.		
1.	Supplying and laying No. 7/.036 SWG twin conductor paper insulated lead covered, double steel tape armoured, jute served, underground cable suitable for 1,000 volts pressure, in a trench 3 ft. deep surrounding the same with 3" of fine sand, enclosing the ends of the cable in indoor and pole type cast iron junction boxes filled with insulating compound and exposed portion of the cable at the pole end in 18 ft. of 1½" galvanised pipe with bend supported with the rail using necessary clamps and No. 7/.036 SWG 660 volt grade insulated wire and accessories	Ft.	150
2.	Running mains in ¾" W. I. pipe using No. 7/.036 SWG insulated wire 660 volts grade and accessories	Ft.	5
3.	Earthing	Item	
	Part II—Interior Work—Station Building.		
1.	Supplying, fixing and wiring T. W. board 21"×18"×1" with battens and rear board equipping it with a 10 amp. D. P. S. T. iron clad switch with fuses, one 2-way D. P. Home office pattern 10 amp. per way distribution box with 5 amp. circuit switches using No. 7/.036 and 3/.029 SWG insulated wire and accessories	No.	1
2.	Do do twin and triple conductor, lead covered, No. 14 B. & S. cable with bended wire for drop lights complete with 2' plate reinforced bakelite ceiling rose, flexible cord, B. C. C. G. reinforced bakelite holder 5 amp. single pole control switch with reinforced bakelite cover round bakelite junction boxes, with insulated terminals, T. W. fillets and accessories	No.	3
3.	Supplying, fixing and wiring in twin and triple conductor, lead covered No. 14 B. & S. cable with bonded wire, for oxidised copper brackets 6"×½" with B. C. lamp holder, etc., as per specification above	No.	5
4.	Do do for ⅜" braized 'silverlac' conduit pendents 2 to 4 ft. long complete with stout ceiling plates, B. C. lamp holder, etc., as per specification above	No.	4
5.	Do do for water tight fittings complete with cast iron reflector, well glass B. C. lamp holder, goose neck, etc., as per specification above		1
6.	Supplying and fixing shades tin enamelled 10"×5"		5
7.	Do do. white opal 10"		7
8.	Do do lamps 220 volts B. C. 40 to 60 watts gas filled		13
9.	Earthing	Item	1
	Part III—Installing light to latrine.		
1.	Supplying, fixing and wiring in a teakwood block 9"×6" with battens and rear board equipping it with a D. P. linked switch 5 amp. protected by a pair of 5 amp. fuse cut outs, tapping from the lighting circuit using necessary length of 3/.029 SWG. L. C. cable with bonded wire, and bakelite round junction box with insulated terminals, etc.	No.	1
2.	Supplying and fixing 2 pin outrigger complete with bolts, etc.		1

	Particulars		Quantity
3.	Supplying, fixing and tarring S. M. rails 24 ft. long		2
4.	Do 2 pin S. C. A. complete		2
5.	Do shackle insulators with straps, etc.		4
6.	Supplying and stringing bare copper wire No. 8 B. & S.	Lbs.	23
7.	Supplying, fixing and wiring in $\frac{5}{8}$" braized conduit with necessary bends, clamps, etc., for reinforced bakelite B. C. lamper holder back plate type complete with tin enamelled shade 60 watt 230 volt B. C. lamp, lamp lock, etc., using 3/.029 SWG. insulated wire and accessories	No.	1
8.	Earthing	Item	

Part IV—Installation of lights to the platform.

1.	Supplying and fixing 10 amp. D. P. iron clad switch with fuses on the existing distribution board using No. 7/.036 SWG insulated wire and accessories	No.	1
2.	Supplying, and running sub-mains in 7/.036 SWG twin conductor lead covered cable with bonded wire, using T. W. fillets and accessories	Ft.	70
3.	Supplying and laying No. 7/.036 SWG twin conductor paper insulated, lead covered, double steel tape armoured jute served underground cable as per specification against item 1 of Part I	Ft.	75
4.	Supplying and setting rails 24' long in cement concrete	No.	4
5.	Do 2 pin S. C. A. complete	No.	4
6.	Do shackle insulators with straps	No.	8
7.	Supplying and stringing copper wire No. 8 B. & S.	Lbs.	41
8.	Supplying, fixing and wiring on $\frac{1}{2}$" galvanised pipe bracket steel dispersive reflectors 14" with B. C. lamp holder, etc., controlled by a single pole ironclad W. T. switch 5 amp. mounted at a height of 6 ft. from the ground level, using necessary length of $\frac{1}{2}$" braized conduit No. 14 B. & S. insulated wire and accessories	No.	4
9.	Supplying and fixing lamps 100 watts 230 volts B. C. gas filled	No.	4
10.	Earthing	Item	

M. HAYATH,
Superintendent.

OFFICE OF THE DEPUTY COMMISSIONER, MYSORE DISTRICT, MYSORE.

(EXCISE DEPARTMENT.)

Notice, dated the 8th July 1938.

The Excise Commissioner's Notification No. A1-1718—37, dated 1st July 1938, as published in *Mysore Gazette*, dated 7th July 1938 at page 1149, supersedes this Office Notification No. K1-662-37, dated 4th July 1938, regarding the sale of Foreign Liquors in the "Retail Off" shop in the Mysore City.

M. G. MEHKRI,
Deputy Commissioner.

MYSORE STATE RAILWAY.

OFFICE OF THE DISTRICT TRAFFIC SUPERINTENDENT, MYSORE.

Notification No. T. M. 44—38, dated 8th July 1938.

The public are hereby informed that the right of selling refreshments, fruits, etc., for the year 1938-39 at Ambuga Railway Station, will be sold by public auction at Ambuga Station on 19th July 1938 at 11 hours by the Traffic Inspector, Mysore State Railway, Mysore.

The successful bidder will have to deposit the full amount of bid immediately the bid is accepted by the Traffic Inspector, with an additional sum of annas ten required for the execution of Bond Form, failing which it will be re-auctioned at his risk. He should also furnish a list of refreshments to the Traffic Inspector with rates of selling.

The sale is subject to the confirmation of the Traffic Manager, Mysore State Railway, Mysore, whose decision is final. He is not bound to accept the highest or any bid and may reject any bid without assigning any reason.

MIR ENAYETH HUSSAIN,
District Traffic Superintendent.